

原书缺封面

电机与控制学报

第 18 卷 第 5 期 (总第 115 期) 2014 年 5 月

目 次

三相并联混合有源电力滤波器的无源控制策略	丁青青, 鲁伟, 徐长波, 李春文	(1)
摆动喷管的 Terminal 滑模鲁棒控制	王卫红, 孙良桦, 张武龙	(7)
断续电流模态隔离型高压开关电路	章治国, 周林, 杨明, 郭珂	(13)
交联聚乙烯绝缘高压直流电缆电场分布计算	叶信红, 韩宝忠, 黄庆强, 赵洪, 杨佳明	(19)
一种交流逆变器死区效应半周期补偿方法	黄文卿, 张兴春, 张幽彤	(24)
环形永磁体夹置式混合励磁无刷爪极发电机的研究	乔东伟, 王秀和, 朱常青	(30)
电力变压器绕组短路电动力计算	徐永明, 郭蓉, 张洪达	(36)
一种表贴式永磁电机磁极结构优化研究	张炳义, 贾宇琪, 李凯, 冯桂宏	(43)
LLC 谐振电路无传感器同步整流控制策略	刘和平, 李金龙, 苗轶如, 彭东林	(49)
一种高功率密度的二自由度电磁执行器	常思勤, 李波, 林树森	(56)
IGBT 开关机理对逆变器死区时间的影响	罗毅飞, 刘宾礼, 汪波, 唐勇	(62)
基于单神经元自适应 PID 的无刷直流电机反电势与磁链观测及无位置传感器直接转矩控制	潘雷, 孙鹤旭, 王贝贝, 董砚	(69)
加入死区作用范围闭环的三电平整流器谐波抑制	宋崇辉, 李坤, 边春元, 孟凡红	(76)
无人机着陆滑跑数学模型与纠偏控制	郝现伟, 杨业, 贾志强, 王勇	(85)
基于锚链切换的平台自动锚泊定位系统设计	金鸿章, 苏晓宇, 于安才, 林峰	(93)
电液伺服系统位置和力模糊切换控制方法	高炳微, 邵俊鹏, 韩桂华	(99)
轴流式人工心脏泵混合磁悬浮系统的耦合特性	李红伟, 范友鹏, 张云鹏, 刘淑琴, 关勇	(105)
H 桥逆变器 IGBT 开路故障诊断方法研究	杨晓冬, 王崇林, 史丽萍	(112)

期刊基本参数:CN 23-1408/TM*1997*m*A4*120*zh*P*¥15.00*2000*18*2014-05*n

责任编辑:刘琳琳

英文审校:姜毓锋

ELECTRIC MACHINES AND CONTROL

Vol. 18 No. 5 May 2014

CONTENTS

Passivity-based control of a three-phase shunt hybrid active power filter	<i>DING Qing-qing, LU Wei, XU Chang-bo, LI Chun-wen</i>	(1)
Terminal sliding mode robust control for swing nozzle	<i>WANG Wei-hong, SUN Liang-hua, ZHANG Wu-long</i>	(7)
Isolated switching circuit based on DCM for high-voltage power supply applications	<i>ZHANG Zhi-guo, ZHOU Lin, YANG Ming, GUO Ke</i>	(13)
Simulation of electrical field distribution of XLPE insulated HVDC cable	<i>YE Xin-hong, HAN Bao-zhong, HUANG Qing-qiang, ZHAO Hong, YANG Jia-ming</i>	(19)
Inverter dead time compensation method based on half PWM period control	<i>HUANG Wen-qing, ZHANG Xing-chun, ZHANG You-tong</i>	(24)
Study on a hybrid excitation brushless claw-pole alternator with an annular PM between the claw poles	<i>QIAO Dong-wei, WANG Xiu-he, ZHU Chang-qing,</i>	(30)
Calculation of electrodynamic force with winding short-circuit in power transformers	<i>XU Yong-ming, GUO Rong, ZHANG Hong-da</i>	(36)
Study on magnetic pole structure of surface mounted PMSM	<i>ZHANG Bing-yi, JIA Yu-qi, LI Kai, FENG Gui-hong</i>	(43)
Sensorless synchronous rectifier control strategy used in LLC resonant circuit	<i>LIU He-ping, LI Jin-long, MIAO Yi-ru, PENG Dong-lin</i>	(49)
High power density of two degree of freedom electromagnetic actuator	<i>CHANG Si-qin, LI Bo, LIN Shu-sen</i>	(56)
The influence of IGBT switching mechanism on the dead-time of inverters	<i>LUO Yi-fei, LIU Bin-li, WANG Bo, TANG Yong</i>	(62)
Back-EMF and flux observation based on single neuron adaptive PID and sensorless direct torque control for brushless DC motor	<i>PAN Lei, SUN He-xu, WANG Bei-bei, DONG Yan</i>	(69)
Harmonic suppression for three-level rectifier with added closed-loop control of the dead-zone working range	<i>SONG Chong-hui, LI Kun, BIAN Chun-yuan, MENG Fan-hong</i>	(76)
Mathematic model and deviation-correction control for UAV taxiing	<i>HAO Xian-wei, YANG Ye, JIA Zhi-qiang, WANG Yong</i>	(85)
Design of automatic mooring positioning system based on mooring line switch	<i>JIN Hong-zhang, SU Xiao-yu, YU An-cai, LIN Feng</i>	(93)
Fuzzy switching control between position and force for electro-hydraulic servo system	<i>GAO Bing-wei, SHAO Jun-peng, HAN Gui-hua</i>	(99)
Coupling in hybrid magnetic levitation system of axial-flow blood pump	<i>LI Hong-wei, FAN You-peng, ZHANG Yun-peng, LIU Shu-qin, GUAN Yong</i>	(105)
Study of IGBT open-circuit fault diagnosis method for H-bridge inverter	<i>YANG Xiao-dong, WANG Chong-lin, SHI Li-ping</i>	(112)

Serial parameters: CN 23-1408/TM * 1997 * m * A4 * 120 * zh * P * ¥15.00 * 2000 * 18 * 2014-05 * n

Responsible Editor: *LIU Lin-lin* **English Examiner:** *JIANG Yu-feng*

原书缺封底