

# 节能

ISSN1004-7948

CN21-1115/TK

# 3

# 2016

ENERGY CONSERVATION

第35卷 第03期 (总第402期)

## ● 密闭式冷凝水回收技术

## ● 低位热力除氧技术

国家发改委“最佳节能实践”案例源企业  
蒸汽热力系统节能技术设备专业服务公司

当热力系统领域里最好的医生

做热力系统领域里最佳的药品

是热力系统领域里最真的伙伴

### 服务范围:

- 密闭式高温冷凝水回收成套装置
- 低位热力除氧器成套装置
- 工业乏汽回收与利用成套装置
- 锅炉自动排污成套装置
- 蒸汽喷射热泵系列
- 高效节能疏水阀系列
- 热力系统诊断、评估及优化集成

○十五年的技术实践经验, 近四百家的应用客户业绩, 节能率15%~30%, 投资回收期3~6个月

○全国十几家代理机构、7个办事处, 组成快捷、周到的销售及网络

○可按世行“合同能源管理”模式进行项目操作

○专利证书号: ZL93213495.5



ISSN 1004-7948



单位名称: 大连汇能科技股份有限公司

地址: 大连市软件园路80号大连理工大学科技园大厦B座301室

联系人: 徐昶斗 邮编: 116023

电话: 0411-84890011 84890033 传真: 0411-84890022

http://www.dl-hn.com

E-mail: xcd8489@163.com

# 节能 (月刊)

Jieneng

中国核心期刊(遴选)数据库全文收录期刊  
中国学术期刊综合评价数据库(CAJCED)统计源期刊  
中国期刊全文数据库(CJFD)全文收录期刊  
中文科技期刊数据库全文收录期刊  
1981年创刊 第35卷第3期(总第402期)  
2016年3月15日出版

主管:辽宁省科学技术厅  
主办:辽宁省科学技术情报研究所  
辽宁省能源研究会  
主任/主编:金娜  
副主任:王建成  
责编:董媛媛 赵博  
编辑:佟昕  
编辑部电话:(024)83186050  
广告部电话:(024)83186053  
主编室电话:(024)83186051  
传真:(024)83186052  
电子信箱:jienerg1981@vip.sina.com  
网址:www.jieneng1981.cn  
出版:《节能》杂志社 邮编:110168  
地址:沈阳市浑南新区朗月街2甲号  
印刷:沈阳中科印刷有限责任公司  
订阅:全国各地邮政局  
国内发行:辽宁省邮政公司报刊发行公司  
国外发行:中国国际图书贸易总公司  
邮发代号:8-150 国外:M5170  
刊号:ISSN1004-7948  
CN21-1115/TK  
广告经营许可证号:2101001500026  
开户名:辽宁省科学技术情报研究所  
开户行:盛京银行沈阳市火炬支行  
账号:070310300100309004254  
定价:每期10.00元 全年120.00元



扫描二维码  
获得更多《节能》资讯

## 目次

### 论坛

- 大连市“十三五”能源结构调整研究 ..... 朱严初(4)  
新疆节能减排现状及对策分析 ..... 孙琴,王哲(9)  
CNG加气站安全隐患及其技术评价 ..... 肖东(15)

### 研究与探讨

- 无机陶瓷平板膜处理生活污水试验研究 .....  
..... 杨若绅,明月(18)  
提高主再热汽温对600MW亚临界空冷机组运行特性的影响  
分析 ..... 付喜亮,刘吉,赵志宏,等(22)  
整体煤气化联合循环发电(IGCC)热力特性分析 .....  
..... 王治亚,何理,张垚,等(27)  
基于等效焓降法的1000MW机组不同工况下的热经济性分析  
..... 程毅,王炯(31)  
污水生物除磷脱氮新技术探讨与展望 ..... 苏雷,陈昊(36)  
摆动式旋转叶轮管内插入物强化传热、除垢和阻力特性研究  
..... 乔尚游(39)

### 电力行业节能

- 基于抽水蓄能电站调度的电力系统节煤减排效应分析 .....  
..... 吕朝阳,李星锐(42)  
国产600MW凝汽机组供热改造方案研究 ..... 肖冰(47)  
电厂实时主蒸汽压力优化软件开发 .....  
..... 许利峰,查庆贵,李平强,等(53)  
电站锅炉烟气余热回收改造施工组织管理实践 .....  
..... 宋卫华(57)

### 建筑行业节能

- 变频VRV空调系统的应用及施工方法 .....  
..... 骆玉海,李永斌,贾永浩,等(59)

### 冶金行业节能

- CGL卧式退火炉余热回收实践 .....  
..... 喻之昂,陈中,张大宝,等(62)  
高温超高压技术在煤气发电中的应用 ..... 唐美琼,赵波(65)

### 热点技术

- 烟气余热回收技术节能与环保经济性分析 .....  
..... 陈丽萍,王万江,齐典伟,等(68)

### 节能设备

- 间歇性设备电机节能研究分析 .....  
..... 谢志山,王吉栋,严寒松,等(73)  
环形金属纤维中餐灶燃烧器的实验研究 .....  
..... 李广鹏,李彬(77)

**Energy Conservation (Monthly)**

**Sponsor:** Liaoning Provincial Institute of Science and Technology Information

**Publisher:** Energy Conservation Magazine Publishing House

**Chief Editor:** JIN Na

**Address:** Lang Yue Street No. 2A, Hunnan District, Shenyang City, Liaoning Province, China

**Post Code:** 110168

**CONTENTS**

Mar. 2016 Vol. 35, No. 3 Total Issue No. 402

**A study of Dalian city's energy structure adjustment during the 13th Five-year Plan**

ZHU Yan-chu

(School of Energy and Power Engineering, Dalian University of Technology, Dalian 116000, China)

**Abstract:** By analyzing the energy present situation in Dalian and demand of global urbanization, the paper put forward the Dalian's energy demand forecast during the 13th Five-year Plan, study the direction of the future energy structure adjustment in Dalian and major energy infrastructure layout combined with the current development demand of energy conservation and emissions reduction and control environmental pollution, provide the basis for the 13th Five-year Plan energy plan of Dalian city.

**Key words:** energy present situation; energy demand; demand forecast; structure adjustment

4

**Treatment of domestic wastewater using inorganic plate ceramic membrane**

YANG Ming-shen, MING Yue

(Municipal and Environmental Engineering College, Shenyang Jianzhu University, Shenyang 110168, China)

**Abstract:** Inorganic plate ceramic membrane bioreactor was used in the treatment of domestic wastewater. The experimental results show that: With a ideal effect of removing, the COD in the pilot system can be removed by over 75%, the removal rate of  $\text{NH}_4^+ \text{-N}$  steady at around 80%, and the removal rate of TP to an average of 33.54%. The effect of removing is ideal; The foul membrane can be washed using HCl solution with 0.1 mol/L of substance concentration after 12 h.

**Key words:** inorganic plate ceramic membrane; domestic wastewater; COD;  $\text{NH}_4^+ \text{-N}$ ; TP; membrane cleaning

18

**Analysis of improving primary and reheat steam temperature's influence on the operating characteristics of 600MW subcritical air cooling unit**

FU Xi-liang, LIU Ji, ZHAO Zhi-hong, et al

(Inner Mongolia Jing Long Power Generation Corporation Limited, Fengzhen 012100, China)

**Abstract:** For high coal consumption of subcritical air-cooled unit during actual operation, the rehabilitation program of increasing the primary and reheat steam temperature was proposed in this paper. Taking a typical 600MW subcritical air-cooled unit as example, a detailed analysis of the impact of the primary and reheat steam temperature change on operating characteristics of the unit and economic performance of increasing steam initial parameter from the thermodynamic point were performed. On this basis, the impact of steam initial parameter on the unit's energy consumption at different conditions was calculated. The results showed that: for case unit, at 100% THA condition, when the primary and reheat steam temperature increased from 538 °C to 580 °C, the power generation efficiency can be increased by 0.61% and unit power supply coal consumption can be reduced 4.73 g/kWh. The energy-saving effect is remarkable. And with the decrease of the load, thermal performance of the unit will be further enhanced. When the load changed at 80% ~40% THA working conditions, supply coal consumption of the unit when improving the steam's initial temperature can be reduced by 5.00 ~5.70 g/kWh.

**Key words:** subcritical; air cooling unit; primary and reheat steam temperature; operating characteristics

22

**Thermal characteristics analysis of integrated gasification combined cycle**

WANG Zhi-ya, HE Li, ZHANG Yao, et al

(Renewable Energy School, North China Electric Power University, Beijing 102206, China)

**Abstract:** In order to achieve the thermal characteristic of IGCC system, identify energy loss of each part and put forward the corresponding energy saving measures. In this paper, integrated gasification combined cycle (IGCC) was first completed based on Aspen plus software, then thermodynamic properties in major part were analyzed with the method of exergy analysis. Using Texaco gasifier for coal slurry gasification, normal temperature wet desulphurization and reheat boiler recycling exhaust energy, thermal efficiency is 42.8% and exhaust temperature is 89 °C, meeting standard requirements in power plant thermal efficiency. Results also show that the largest heat loss occurs in gas purification (exergy loss rate is 11.2%, 22.8% respectively), followed by waste heat boiler and gasifier. It's an effective measure to speed up high temperature dry process desulphurization technology or furnace desulfurization in improving thermal efficiency.

**Key words:** IGCC; texaco gasification; thermodynamic analysis; exergy method; combined cycle

27

**Thermal economy analysis of 1000MW unit under different working conditions based on equivalent enthalpy drop method**

CHENG Yi, WANG Jiong  
(AN GANG GROUP, Anyang 455003, China)

**Abstract:** China is a big country of energy production and consumption, so energy-saving and reducing pollution is imperative, when energy becomes more and more prominent. Using energy effectively and thermal economy have a great practical significance. The paper takes the THA and 50% THA conditions of the N1000MW unit as the example to analyze and compare the thermal economy of the unit with the equivalent enthalpy drop method. The purpose is to get the pumping efficiency for analyzing the energy utilization degree. From the calculation results of thermal economy, the exchanger No. 8 can be transformed in the unit. The paper has certain referential value in the relevant power plant.

**Key words:** energy-saving; thermal economy; equivalent enthalpy drop method

31

**Analysis of coal saving and emission reduction effect of power system based on the regulation of pumped storage power station**

LV Chao-yang, LI Xing-rui  
(Wuhan University, Wuhan 430071, China)

**Abstract:** In the world pay more and more attention to the energy and environmental issues of today, the reasonable exploitation and utilization of clean energy has become the consensus of the construction of energy in the world, where the pumping energy storage power station with mature technology, peak shaving, adjustable pressure characteristics of strong function of PM, in the world the development of clean energy construction recognized. Pumped storage power plant development and operations management in climate change diversity, coal saving face high requirements under the new situation, scientific reasonable arrangements for pumped storage power dispatch mechanism, scientific and reasonable arrangements for pumped storage location in the power system, and give better play to the pumped storage power station coal saving effect. This paper mainly through the pumped storage to different operation schemes of the power plant are analyzed, and analyzed under the different load curve characteristics of pumped storage can work position difference, analysis with pumped storage power to work in different ways, analysis the influence of power system in other power operation mode ring, and then analyzes the consumption of coal in the power system. The theoretical significance and practical value of the research results can provide reference for the sustainable development and construction of pumped storage in China.

**Key words:** pumped storage; power system; coal saving

42

**Software development of real time main steam pressure optimization in power plant**

XU Li-feng, ZHA Gui-qing, LI Ping-qiang, et al  
(Jiuhua Power Plant in Chizhou City Anhui Province, Chizhou 247100, China)

**Abstract:** In order to achieve the purpose of energy saving and consumption reduction, a real-time optimization system of main stream pressure is developed for 300MW large thermal power generating units. The method of unit operation state reconstruction is put forward based on the matrix equation of thermal system. The calculation accuracy of the model is improved on the basis of the rule of operating parameters by a hybrid modeling method based on mechanism analysis and statistical method. Finally, Delphi programming and MySQL database are utilized to realize real-time optimization of thermal unit main stream pressure and to guide the power unit operation. The software application shows that the constant pressure is adopted between the 100% load and the 80% load, and the sliding pressure is adopted below the 80% load. The heat consumption is gradually decreased with the increase of the load.

**Key words:** real-time optimization; thermal power unit; mixed modeling; main stream pressure

53

**Economic analysis of energy saving and environmental protection of flue gas waste heat recovery technology**

CHEN Li-ping, WANG Wan-jiang, QI Dian-wei, et al  
(School of Architecture Engineering, Xinjiang University, Urumqi 830047, China)

**Abstract:** Flue gas waste heat recovery technology has the advantages of energy saving, emission reduction, water saving. In order to reduce the using of natural gas in Urumqi, established a calculation model, which is based on the thermodynamics theory and combustion theory; Using the gas source of Urumqi, which including Central Asia gas and Karamay gas, as calculation basis. Calculated the amount of gas saving, the amount of water saving, the amount of the reducing of harmful gas emissions, and the improve efficiency of the gas-fired boilers when they used the flue gas waste heat recovery technology. According to analyzing the results of calculation, it shows that using flue gas waste heat recovery technology can improve the efficiency of boiler about 17.36%. It means that, about 169.0573 million Nm<sup>3</sup> nature gas can be saved per year Nm<sup>3</sup>, and about 883.3 thousand tons water can be saved as well. What is more, by using flue gas waste heat recovery technology can reduce the emission of harmful gas: 53.12 ~ 195.65t of NO<sub>x</sub> and 1210.22 ~ 3462.57t of CO<sub>2</sub> emissions can be reduced. From the data above, it shows that, the social and economic benefit by using flue gas waste heat recovery technology is very large, thus it can be applied to the heating gas boiler in Urumqi.

**Key words:** gas-fired boiler; flue gas condensation; waste heat recovery; heat efficiency

68

# 密闭式蒸汽冷凝水回收技术 浮球型双金属疏水阀系列产品

## 三十年技术积淀 成就厚重品质



### 技术特点

- ★回收装置可以无汽蚀地泵送高达 150℃ 凝结水。
- ★经过计算的冷凝水靠背压输送，稳定可靠，热损失小，无污染。
- ★自主研发的疏水阀，使用寿命相当于国标的 2 倍，可提高蒸汽利用率。
- ★结合各行业经验的二次闪蒸汽解决方案，使热能充分利用。



### 广泛应用

- ★化工行业、橡胶行业、木材加工行业。
- ★啤酒行业、造纸行业、粮食加工行业、油脂行业。
- ★烟草行业、制药行业、棉纺行业、印染行业。

### 显著的效果

- ★节能率可达 20%~30%。
- ★比开放式回收能效提高 1 倍以上。
- ★投资回收期 3~6 个月。

### 优质的服务

- ★整体技术咨询和系统方案论证。
- ★个性化工艺选择和最优系统设计。
- ★现场开车调试和人员培训。
- ★整个生命周期的技术支持和配件供应。

### 可靠的全系列产品

- ★高温冷凝水回收泵站。
- ★高温冷凝水回收装置。
- ★防汽蚀喷射回路。
- ★浮球型双金属疏水阀。
- ★自力式压力调节阀。
- ★止回阀。



辽宁省能源研究所  
国家蒸汽冷凝水回收技术推广中心

地址：辽宁省营口市西市区银泉街 65 号 邮编：115003  
电话：0417-2839119 2832419 2832179  
联系人：乐辉 张雷  
<http://www.lnsnys.com>